

# Indoor Air Quality Display

## CO<sub>2</sub> – Temperature – RH - Clock



### Wim serie

Sizes(lxbxh)	mm
Wim300	300 x 225 x 40
Wim390	390 x 300 x 40
Wim530	530 x 220 x 40
Wim720	720 x 570 x 40

### IAQ Monitor WIM390

Size : 390mm x 300mm x 40mm  
 Display size : CO<sub>2</sub> : 71mm, others : 28mm  
 Mounting : Wall mounting  
 GOOD NORMAL POOR : CO<sub>2</sub> level with back-light.  
 Power : 220V/110VAC 12VDC  
 Material : Coated Temper Glass with aluminium frame

CO<sub>2</sub> range : 0 - 10000ppm  
 Temperature : -20.....+50°C  
 Rel. Humidity : 0 - 100%RH

### Output:

AN1 : CO<sub>2</sub> Output : 4-20mA(=0-3000ppm)  
 AN2 : Temperature output : 4-20mA(=0-50°C)  
 AN3 : Rel. Humidity output : 4-20mA(=0-100%RV)  
 RS232 : Communication for CO<sub>2</sub>/Temperature and Rel. Humidity  
 Optie : RS485 communication for CO<sub>2</sub>/Temperature and RH  
 Optie : ZigBee wireless communication



Model WIM530



[www.meten.nl](http://www.meten.nl)

##### Tel. (0297)-325836